METHOD AND SYSTEM FOR PRODUCING ALLOY WHEELS FOR MOTOR VEHICLES

TECHNICAL FIELD

5   The present invention concerns a method for producing alloy wheels.

BACKGROUND ART

Alloy wheels are being increasingly used in the automobile industry to equip both cars and small and

10   medium-sized commercial vehicles and they are particularly appreciated because, besides giving the motor vehicle a particularly attractive appearance, they present mechanical characteristics, such as light weight and rigidity, that are decidedly better with respect to

15   wheels made in the traditional way.

An alloy wheel presents an axle and comprises a hub, a rim, which are situated concentrically around the axle and an intermediate portion, which has the function of

20   connecting the hub to the rim and is made in a very high number of models to give each wheel a distinctive character. Generally, the aforementioned models of the intermediate portion can be classified in a first family, according to which the hub and the rim are

25   connected by a plurality of spokes, and in a second family, according to which the hub and the rim are connected by a perforated plate. Moreover, alloy wheels

are made both in a single piece, that is the hub, the rim and the intermediate portion are formed of a single piece obtained by casting or by forging, and in a number of pieces, generally two, that is the hub, a part of the

5   rim and the intermediate portion are made in a first piece obtained by casting or forging, while a further part of the rim is made separately, also by casting or forging, in a second piece, which is later assembled with the first piece. The alloy wheel formed of several

10   pieces is usually defined as being of compound type.

In both cases, the realisation of an alloy wheel contemplates a procedure of casting an alloy of aluminium or magnesium to make an untreated wheel or the

15   pieces that make up the wheel, a heat treatment and a first and a second machining with a turning lathe. As an alternative to casting, the wheel is forged and, afterwards, subjected to heat treatment. The machining operations have the function of realising finished

20   surfaces with high degrees of tolerance along the rim to guarantee a perfect coupling with the tyre and at the hub in the coupling area with the end part of an axle or of a semi-axle of a motor vehicle. The machining also has the function of eliminating burrs and of correcting

25   any imprecisions derived from the previous operations. In other words, the untreated wheel presents eccentric masses which must be removed in such a way that the

finished wheel, in use, is as balanced as possible in rotation around its own axis so as not to transmit vibrations to the motor vehicle.

Whereas said result was once accepted as satisfactory by

5   the automobile industry, car manufacturers are now beginning to demand decidedly higher levels of balancing in alloy wheels since car manufacturers are, on the one hand, obliged to reduce the lead weights used for balancing wheels for environmental reasons and, on the

10   other hand, to offer ever higher levels of comfort.

DISCLOSURE OF INVENTION

The aim of the present invention is to provide a method for producing alloy wheels which is able to achieve

15   balancing levels decidedly superior to those that can be obtained with the known methods without substantially increasing the production costs.

According to the present invention a method is supplied

20   for producing alloy wheels according to claim 1.

The present invention concerns a system for producing alloy wheels for motor vehicles.

25   According to the present invention a system is realised for producing alloy wheels for motor vehicles according to claim 15.

- 4 -

BRIEF DESCIPTION OF THE DRAWINGS

For a better understanding of the present invention, a preferred embodiment will now be described, purely as an example without limitation, with reference to the enclosed figures, in which:

- figure 1 is a front elevation view on a reduced scale of a light alloy wheel;

- figure 2 is a view of a section of the wheel in figure 1 along the section lines II-II;

- figure 3 is a view on an enlarged scale of a detail of the wheel in figure 2;

- figure 4 is a schematic view of a geometric representation of the mass to be removed from the wheel in figure 1;

- figure 5 is a view of a block diagram which sums up the phases of the method to which the present invention refers;

- figure 6 is a schematic view of a side elevation of a cutting machine tool for machining the wheel in figure 1, realised according to the present invention;

- figure 7 is a view on an enlarged scale of a detail of the machine in figure 6 according to a variation of the present invention; and

- figure 8 is a variation of the block diagram in figure 5.

BEST MODE FOR CARRYING OUT THE INVENTION

With reference to figures 1 and 2, the reference 1

indicates overall a substantially finished wheel, that
is obtained by means of known processes of casting a
metal alloy or of forging, subsequently subjected to
heat treatment and machining. The wheel 1 comprises an
axle 2 around which extend a hub 3 with a central hole
4, a rim 5 suited to house a tyre, not illustrated in
the enclosed figures, and an intermediate portion 6
which in the illustrated example is defined by seven
spokes 7, which are uniformly distributed around the
axle 2 and connect the hub 3 to the rim 5. In the
example illustrated in the enclosed figures reference is
made to a wheel 1 made all in one piece with an
intermediate portion 6 defined by seven spokes 7; of
course the present invention extends to any type of
wheel, in one piece or compound, and to any type of
intermediate portion.

As better illustrated in figure 3, the rim 5 presents a
substantially cylindrical wall 9 laterally delimited by
two annular edges 9 and 10, which together with the wall
8 define a channel 11 suited to contain a tyre not
illustrated in the enclosed figures. The wall 8
presents a face 12 facing towards the outside and along
which will be performed the interventions for balancing
the wheel 1. Moreover, (fig. 1 and 2) the wall 8 is
crossed by a hole 13, which is suited to house the valve
of the tyre, not illustrated in the enclosed figures.

In brief, the method according to the present invention contemplates determining the unbalance of the wheel 1 by the phases of measuring the unbalance and of checking the acceptability of the unbalance. If the unbalance

5   does not fall within parameters considered acceptable, then the method calculates the coordinates of a mass to be removed and removes the mass by machining.

With reference to figure 5, in the acquisition block 14

10   characteristic signals of unbalance are acquired, while in the calculation block 15 the mass M and the phase F of the unbalance are calculated. The mass M represents the mass to be removed to balance the wheel, while the phase F is the angular reference, from which the mass M

15   must be removed, with respect to a determined point of reference of the wheel 1. In the block 16, the mass of the valve MV (which will be installed on the wheel 1) and the phase of the valve FV with respect to the determined point are extracted from a memory not

20   illustrated. In the block 17, a simulation is made of the unbalance in working conditions of the wheel 1 as though the valve were fitted on the wheel 1 and the simulated mass MS to be removed and the relative simulated phase FS are calculated. In the block 18, a

25   value M_{max} of the maximum acceptable unbalance is extracted from the memory and in the block 19 it is checked whether the mass MS is lower than the value

M_{max}. If this condition is found, in the block 20 a signal of acceptability A of the wheel 1 is given. If, on the contrary, the condition of block 19 is not found, then it is necessary to remove the mass MS from the

5   wheel 1. For this purpose the following data are extracted from the memory in the block 21; specific weight PR of the material of the wheel 1, the geometry GR of the wheel 1, the allowed zones of removal ZL and the type of machining LT chosen for removing the mass

10   MS.

In the block 22, the geometry G of the mass MS to be removed is calculated, while in the block 23 the coordinates C of the geometry G are calculated with

15   respect to a point of reference.

In order to avoid unattractive machining on the wheel 1, the geometry G of the mass MS is distributed along a relatively large angle α, as illustrated in figure 1 and

20   in figure 4 which represents an example of the geometry G of the mass MS to be removed from the wheel 1. The coordinates C are transferred to a cutting machine tool with numerical control which removes the mass MS from the wheel 1.

25

The method described contemplates different possibilities of implementation. The first consists of

- 8 -

carrying out the finishing operation on a cutting machine tool, checking the unbalance and if necessary calculating the coordinates C of the mass MS to be removed in order to correct the unbalance on a machine

5   for measuring unbalance, and correcting the unbalance on a cutting machine tool. The second possible implementation lies in the fact that the finishing operation, checking and possible calculation of the coordinates C are carried out on the same cutting

10 machine tool, while the correction of unbalance is carried out on another cutting machine tool. Lastly, the third possible implementation is certainly the most advantageous because the finishing, the determination of the unbalance and the correction of the unbalance are

15 all carried out on a single cutting machine tool.

With reference to figure 6, a cutting machine tool 24 is illustrated which is suited to operate according to the method described for finishing, checking the unbalance

20 and eventually correcting the unbalance in a single machine.

The machine tool 24 comprises a base 25, which supports a piece holding chuck 26, which is motor-driven and

25 rotates around an axle 27, and a frame 28, which supports a slide 29 moving along a horizontal axis X1 with respect to the frame 28, a slide 30 moving along a

vertical axis Z1 with respect to the slide 29, a third
slide 31 moving along a horizontal axis X2 with respect
to the slide 30. The slide 31 supports a motor-driven
chuck 32 rotating around a horizontal axis 33 and suited

5   to support a tool 34. Substantially, the machine tool
24 is able to carry out milling and turning operations,
or both processes simultaneously. The machine tool 24
also comprises a control unit 35, sensors 36 for
detecting static unbalance (accelerometers or

10   velocimeters), sensors 37 for detecting the angular
position (encoder) of the chuck 26 and a numerical
control 38. The control unit 25 carries out all the
operations described in the block diagram in the figure
and transfers the coordinates C to the numerical control

15   38 which controls the shifting of the tool 34 according
to the angular shifting of the wheel 1.

With reference to figure 7, the machine tool 24 is
equipped with further sensors 39 (piezoelectric sensors,

20   load cells, accelerometers) suited to detect the dynamic
unbalance, that is the torque T on the chuck 26 exerted
by the mass M. The block diagram in figure 8 concerns
the operating method of the variation in figure 7. This
method differs from the previous one by the fact that it

25   contemplates the removal of material from the wheel 1 on
two horizontal planes P1 and P2 intersecting the wheel 1
respectively near the edge 9 and the edge 10 (figure 7).

With reference to figure 8, a block 40 is shown for acquiring signals by means of the sensors 36, 37 and 39, a block 41 for calculating the values M, T and F, a block for calculating the mass M1 and the phase F1 for the plane P1 (figure 7) and the mass M2 and the phase F2 for the plane P2 (figure 7); then in the block 43 the values of the mass of the valve MV and of the phase of the valve FV are extracted and in block 44 the mass MS with the respective phase FS1 and the mass MS2 with the respective phase FS2 are calculated as resulting from the simulation of valve presence. In the block 45 the acceptability values $M1_{max}$ and $M2_{max}$ are extracted from the memory and are compared respectively with the values of MS1 and of MS2 in the blocks 46, 50 and 51. If the masses MS1 and MS2 are both lower than $M1_{max}$ and $M2_{max}$ (see blocks 46, 51) the block 50 gives an unbalance acceptance signal A. If the masses MS1 and MS2 are not respectively lower than $M1_{max}$ and $M2_{max}$, then in a similar way to that described for the blocks from 21 to 23 in figure 5, the geometry G1 and the coordinates C1 of the mass MS1 are calculated (blocks 47, 48 and 49), and the geometry G2 and the coordinates C2 of the mass MS2 (blocks 52, 53 and 54). The blocks 47 and 52 are equivalents of the block 21 in figure 5. If only one of the conditions has not occurred, then only the coordinates C1 or the coordinates C2 are calculated. The coordinates thus calculated are transmitted to the

numerical control 38 (figure 6) of the machine tool 24

which carries out the machining to balance the wheel 1.